



The LS371A is a high pressure diecast brass luminaire featuring an IP67 rating. The LED version offers both line voltage and low voltage options, and is ideal where a lower surface temperature is required.

LED version see page 137.


SPECIFICATIONS

Lamp Source	Halogen Bi-Pin QT12 (G4) 20 W
IP Rating	IP67
Construction	Die-cast brass shot blasted standard <ul style="list-style-type: none"> ■ Polished ■ Powder coated black ■ Powder coated silver ■ Powder coated Superchrome
Installation Type	Wall mount
Standard Inclusion	Thermal cutout
Ambient Operating Temperature	-20 °C to +50 °C
Warranty	5 year structural, 1 year electrical
Photometrics	Go to www.lumascape.com.au ▶ Technical Data ▶ Photometric Files

NOTE: Product specifications are subject to change without notice. Any luminaire can become hot - take care with appropriate use and placement.



LS371A Boulevard
Shot blasted brass



CONFIGURE THIS PRODUCT >

LS371	→				A	→		
SOURCE					FINISH			
Lamp	Wattage	Base	Voltage	Code	Description	Code		
Halogen Bi-pin QT12	20 W max	G4	12 V AC ⁽¹⁾	A	Shot blasted standard			
					Polished brass	P		
					Powder coated black	CB		
					Powder coated silver	CS		
					Powder coated Superchrome	CA		

⁽¹⁾ Requires remote transformer - see page 239.